

TEK-MATE

Portable leak detector with heated diode technology at an affordable price.



- Patented heated diode
- Sensitive for all CFC, HCFC and HFC
- Sensitivity: 1 - 2 g/year according to EN 14624 (F-Gas)
- Auto zeroing
- Visual and audio leak indicators
- Hi/Lo sensitivity selector
- Easy one-button operation, ergonomic design
- Water-resitant filter protecting the sensor
- 2 "D"-batteries
- Low battery indicator
- Autonomy: 16 hours

SPECIFICATIONS

Minimum sensitivity	1-2 g/year according to EN 14624
Control	Power: on/off Sensitivity: High/Low
Calibration / Zero setting	Automatic
Weight with batteries	0,700 kg
Power	2D-size (1.5V) alkaline batteries (included)
Battery life	Approx. 16 hours
Probe	Chrome-plated flexible metal, approx. 43 cm
Operating temperature	-20°C to 50°C
Certifications	CE Marking Power Safety and EMC (elektromagnetic compatibility). SAEJ1627
Warranty	2 years

ACCESSORIES

705-202-G1	TEK-Mate
703-080-G10	TEK-Check R-134a reference leak
Replacement parts:	
703-020-G1	Heated diode sensor
705-600-G1	Filters
705-401-P2	Storage case, hard plastic

- Delivered in a hard storage case including; Tek-Mate, 2 "D" batteries, 1 heated diode sensor, filters, operating manual and Verification Journal®.