

New

ROTHENBERGER
pipetool technologies at work



ROREC PRO A3

The new generation of devices for flammable refrigerants



Scan the QR code or visit
rothenberger.com

Explosion-proof

Safe to use for class A1, A2L, A2 and A3 refrigerants.

Maintenance-free and durable

4-pole electric motor guarantees a long service life.

High suction capacity

Oil-free 2-piston compressor ensures complete emptying.



New



ROREC PRO A3

Refrigerant recovery unit

Refrigerant recovery unit with high extraction capacity for complete emptying of refrigeration and air conditioning systems

Application benefits

- Explosion-proof: Suitable for refrigerants of classes A1, A2L, A2 and A3 (e.g. R290)
- Compact design and weight of less than 12 kg
- Digital display and one-button operation
- Maintenance-free operation due to oil-free 2-piston compressor
- 4-pole motor guarantees longevity of the machine
- Automatic shutdown and automatic start as soon as the pressure rises again
- Draining of refrigerant residues through PURGE function

Technical data

Recovery rate	gaseous: 0.5 kg/min; 30 kg/h fluid: 3.5 kg/min; 210 kg/h push/pull: 9.5 kg/min; 570 kg/h
Working area pressure	38.5 bar
Input power	750 W
Frequency	50–60 Hz
Voltage	220–240 V

Digital display

Clearly structured display of the measured pressure values



ATEX-certified

Low pressure switch

Automatic shut-off and automatic restart once the pressure increases again

Oil-free 2-piston compressor

Very high recovery rate with maintenance free operation



Securely attached power cable



Refrigerant filter for safe recovery included in the scope of delivery



Purge function for complete draining of the recovery unit



Model

ROREC PRO A3

Weight

12.000 kg

PU

1

No.

1500004451

Filter

0.120 kg

1

168713

Scope of delivery: Refrigerant recovery unit ROREC PRO A3, filter, filter connection hose, power cable, OFP cable, carrying belt, instruction manual